

Application No. 10/720,481
Reply dated April 8, 2005
Response to Office Action dated December 15, 2004

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (cancelled)

2. (currently amended) An electro-mechanical braking control device comprising:

an electro-mechanical brake for electrically generating a braking force in response to a stroking force or stroking speed of a braking pedal, or a braking operation signal, and

a parking brake mechanism for maintaining the braking force when power is not supplied to said electro-mechanical brake or a control signal thereto is turned off,

wherein when the braking pedal is stroked or the braking operation signal is detected, said parking-brake mechanism is controlled so that the braking force may be maintained by said electro-mechanical brake, and

~~according to Claim 1,~~ wherein, when the braking pedal is stepped on or the braking operation signal is detected, depending on a state of a power supply switch or an ignition key switch of a vehicle, it is determined whether the braking force of said electro-mechanical brake is maintained by said parking-brake mechanism or not.

3. (original) An electro-mechanical braking control device according to Claim 2, wherein, when said power supply switch or said ignition key switch

Application No. 10/720,481
Reply dated April 8, 2005
Response to Office Action dated December 15, 2004

of the vehicle is turned off, the braking force of said electro-mechanical brake is maintained by said parking-brake mechanism.

4-6. (cancelled)

7. (currently amended) An electro-mechanical braking device for electrically generating a braking force in response to a control signal from a control device performing a control processing based on at least one of a stroking force and a stroking speed of a braking pedal, and a braking operation signal.

said electro-mechanical braking device comprising a parking-brake mechanism for maintaining the braking force when power is not supplied thereto or the control signal is not supplied thereto.

wherein said parking brake mechanism is controlled when the braking pedal is stepped on or the braking operation signal is detected, and

~~according to Claim 6,~~ wherein, when the braking pedal is stepped on or the braking operation signal is detected, and a power supply switch or an ignition key switch of a vehicle is turned off, said parking-brake mechanism is activated to maintain the braking force.

8-10. (cancelled)

11. (currently amended) A control method for controlling an electro-mechanical braking device including an electro-mechanical brake for electrically generating a braking force in response to a stroking force or a stroking speed of a braking pedal, or a braking operation signal, and a parking brake mechanism for maintaining the braking force when power is not supplied to said electro-mechanical brake or a control signal is not applied thereto.

Application No. 10/720,481

Reply dated April 8, 2005

Response to Office Action dated December 15, 2004

said control method comprising at least the step of controlling said parking brake mechanism to maintain the braking force of said electro-mechanical brake when the stroking force or stroking speed of the braking pedal or the braking operation signal is detected, or the braking pedal is stepped on or the braking operation signal is provided.

~~according to Claim 10,~~ wherein the step of controlling said parking brake mechanism comprising a step of maintaining the braking force of said electro-mechanical brake when it is detected that a power supply switch or an ignition key switch of a vehicle is turned off.

12. (currently amended) A control method for controlling an electro-mechanical braking device including an electro-mechanical brake for electrically generating a braking force in response to a stroking force or a stroking speed of a braking pedal, or a braking operation signal, and a parking brake mechanism for maintaining the braking force when power is not supplied to said electro-mechanical brake or a control signal is not applied thereto.

said control method comprising at least the step of controlling said parking brake mechanism to maintain the braking force of said electro-mechanical brake when the stroking force or stroking speed of the braking pedal or the braking operation signal is detected, or the braking pedal is stepped on or the braking operation signal is provided.

~~according to Claim 10,~~ wherein the step of controlling said parking brake mechanism comprising a step of activating said parking brake mechanism to cancel the braking force of said electro-mechanical brake, when a power supply switch or an ignition key switch of a vehicle is turned on, and the braking pedal is not stepped on or the braking operation is not performed in accordance with the braking operation signal, and a drive source and a driving axis are connected with each other.

Application No. 10/720,481

Reply dated April 8, 2005

Response to Office Action dated December 15, 2004

13. (currently amended) A control method for controlling an electro-mechanical braking device including an electro-mechanical brake for electrically generating a braking force in response to a stroking force or a stroking speed of a braking pedal, or a braking operation signal, and a parking brake mechanism for maintaining the braking force when power is not supplied to said electro-mechanical brake or a control signal is not applied thereto.

said control method comprising at least the step of controlling said parking brake mechanism to maintain the braking force of said electro-mechanical brake when the stroking force or stroking speed of the braking pedal or the braking operation signal is detected, or the braking pedal is stepped on or the braking operation signal is provided.

wherein the step of controlling said parking brake mechanism comprising a step of activating said parking brake mechanism to cancel the braking force of said electro-mechanical brake, when a power supply switch or an ignition key switch of a vehicle is turned on, and the braking pedal is not stepped on or the braking operation is not performed in accordance with the braking operation signal, and a drive source and a driving axis are connected with each other, and

according to Claim 12, the control method further comprising the step of detecting that an engine speed reaches a predetermined value or exceeds the predetermined value, when it is detected that the drive source is connected with the driving axis.

14. (new) An electro-mechanical braking control device comprising:

an electro-mechanical brake for electrically generating a braking force in response to a stroking force or stroking speed of a braking pedal, or a braking operation signal, and

Application No. 10/720,481

Reply dated April 8, 2005

Response to Office Action dated December 15, 2004

a parking brake mechanism for maintaining the braking force when power is not supplied to said electro-mechanical brake or a control signal thereto is turned off,

wherein when the braking pedal is stroked or the braking operation signal is detected, said parking-brake mechanism is controlled so that the braking force may be maintained by said electro-mechanical brake, and

wherein, when said power supply switch or said ignition key switch of the vehicle is turned off, the braking force of said electro-mechanical brake is maintained by said parking-brake mechanism.